



Xtra-Dry™

Product Specifications

TB:XD01
Page 1 of 2
Revised 4/18/00

DEFINITION: **Xtra-Dry** is a free flowing powder which is added to dry blended feed minerals at the mixing stage. **Xtra-Dry** improves the quality of free choice minerals where weather resistance and anti-caking is desired. When added to the blend, the minerals will repel moisture, reduce leaching of nutrients, and remain free flowing. With **Xtra-Dry**, your customers will have a premium weatherproof mineral product.

MODE OF ACTION: **Xtra-Dry** is a unique blend of ingredients. When added to minerals, **Xtra-Dry** will coat each particle and impart a water repellent barrier.

COMPOSITION: **Xtra-Dry** is a combination of calcium silicate, calcium salts of long-chain fatty acids, silicon dioxide and natural flavors.

APPEARANCE: Free flowing gray powder.

TYPICAL ANALYSIS:

Calcium (Ca)	3.6 to 5.4%
Moisture, maximum	4.6%

BULK DENSITY: 24-28 lbs per cu. ft. (loose)

SOLUBILITY: Insoluble in water

PACKAGING: 40 pound multi-wall, poly-lined, valve packed bags - 40 bags per pallet; 1,600 pounds per pallet

STORAGE AND HANDLING: Store in a cool, dry place. Reseal bags well after each use. Normal precautions should be taken with any dusty conditions during feed manufacturing; wear eye protection and dust mask. See MSDS for more information.

DIRECTIONS FOR USE:

1. Use 10 to 20 lbs **Xtra-Dry** per ton of minerals. The **Xtra-Dry** use rate will depend on the amount of protection desired. Use 10 lbs per ton in the current minerals line and use 15 to 20 lbs per ton for premium, value added products.
2. **Xtra-Dry** should be the last dry ingredient added to the mix
3. If liquid molasses is used, add it before **Xtra-Dry**
4. Add **Xtra-Dry** first if any mineral or vegetable oil is used as a dust suppressant
5. Mix for a minimum of 30 seconds

LABELING RECOMMENDATIONS:

All ingredients should be listed on the feed tag label. All ingredients have AAFCO approval for use in animal feed.